

BENEFITS

- WATER BASED
- ODORLESS
- NON TOXIC
- FREE OF VOC'S
- FREE OF FLAMMABLE SOLVENTS
- EASY TO APPLY
- MULTIPLE USES
- SUPER ADHESIVE (Asphalt shingle)
- CAN BE APPLIED TO ALMOST ANY SURFACES

DESCRIPTION

Aqua-Loc Rubber Guard - Roller/Brush Grade is a highly modified asphalt emulsion. It is a cold applied liquid rubber membrane, single component system that can be used for a multitude of applications.

USAGE

Numerous applications such as Roofing, Roofing Repairs, Corrosion and Rust Protection (most metals), Waterproofing & Concrete Protection (between slabs, basement walls, foundations and more), Automotive (under coatings and noise/vibration transmission), Ponds and Planter Boxes, etc.

ADVANTAGES

- Easy to apply
- High puncture resistance
- Does not allow tracking
- Super Adhesive
- Minimal surface preparation
- Seamless – No laps
- Ozone and UV resistant
- Environmentally friendly
- Fully bonds to most substrates
- Can withstand thermal cycling

LIMITATIONS

Aqua-Loc Rubber Guard - Roller/Brush Grade should not be applied when ambient temperature is below 45°F/7.2°C. Do not apply in the rain or if rain is imminent. Make sure surface is dry and clean of dirt, oil, grease or any debris. Do not store in direct sunlight. Product should be allowed to cure before recoating. Shelf life is 6 months in tightly sealed containers. Uncured product is subject to damage if frozen. Do not apply to wet or frosted surfaces.

APPLICATION

Can be applied with a brush, roller or spray mechanically. Mix product slowly, before and during application. Product will fully cure in 24 hours at 70°F (21°C) 50% relative humidity. Apply in thin coats; allow first coat to dry before reapplying. Curing time is affected by relative humidity and temperature. Product turns from brown (wet) to black (dry). Please call Aqua-Loc Corporation for application methods, etc.

CAUTION

When applying, wear gloves, eye protection and other suitable personal protective equipment. Consult the MSDS for further information.

THIS PRODUCT IS NOT SUBJECT TO THE CONTROLLED PRODUCTS REGULATIONS



GUTTER ON EDGE OF BUILDING
NOT SUITABLE FOR SPRAYING



SEALING A PARPET WALL BEFORE TOP
COAT APPLICATION



SEALING METAL GUTTER JOINT



SEALING CRACKS IN CONCRETE WALLS